

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

DUPLICATE  
FIELD NOTES

Reestablishment of Corner of Secs. 2, 3, 34, and 35,

Ts. 52 and 53 S., R. 30 E.

and

Reestablishment of Corner of Secs. 1, 6, 7, and 12,

T. 58 S., Rs. 37 and 38 E.

Of the Tallahassee Meridian,

In the State of Florida

EXECUTED BY

Willis W. Bandy, Surveyor

Under special instructions dated January 18, 1933, which provided

for the surveys included under Group No. , approved

and assignment instructions dated January 18, 1933

Survey commenced January 25, 1933

Survey completed February 5, 1933

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Reestablishment of cor. of secs. 2, 3, 34, and 35, Ts. 52 and 53 S., R. 30 E.  
and  
of cor. of secs. 1, 6, 7, and 12, T. 58 S., Rs. 37 and 38 E.  
Tallahassee Meridian, Florida

Pursuant to instructions from the Associate Supervisor of Surveys, dated January 18, 1933, for the running of connecting lines to determine the geographic position of established public land surveys in Monroe County, Florida, connecting lines were run in the vicinity of Everglades and Homestead, Florida. The following is a record of the remonumentation of the cor. of secs. 2, 3, 34, and 35, on the line bet. Ts. 52 and 53 S., through R. 30 E., and the cor. of secs. 1, 6, 7, and 12, on the line through T. 58 S., bet. Rs. 37 and 38 E., Tall. Mer., Fla.

The cor. of secs. 2, 3, 34, and 35, on the line bet. Ts. 52 and 53 S., through R. 30 E., is a lightwood post, 4 ft. long, 3 ins. square, south and alongside of which is a concrete monument, 4 ft. long, 4 ins. square, set by county surveyor of Collier County, Fla.

At point for cor.

Set a brass tablet,  $3\frac{1}{2}$  ins. diam., 3 ins. stem, in a cylindrical concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for cor. of secs. 2, 3, 34, and 35, with top mkd

T 52 S	R 30 E
S 34	S 35
S 3	S 2
1933	

from which

The original bearing trees:

A cabbage palm, 10 ins. diam., bears S.  $87^{\circ}$  W., 158 lks. dist., mkd. with 3 hacks.

A cabbage palm, 9 ins. diam., bears N.  $9\frac{3}{4}^{\circ}$  W., 120 lks. dist., with no marks.

And bearing trees marked by local surveyor:

A cabbage palm, 10 ins. diam., bears S.  $24^{\circ}$  W., 69 lks. dist. mkd. T 53 S R 30 E S 3 BT.

A cabbage palm, 9 ins. diam., bears N.  $60\frac{1}{4}^{\circ}$  W., 130 lks. dist., mkd. T 52 N R 30 E S 34 BT.

And a new bearing tree:

A cabbage palm, 9 ins. diam., bears S.  $3\frac{1}{2}^{\circ}$  E., 187 lks. dist., mkd X.

I replace original lightwood post by cor.

The point for cor. of secs. 1, 6, 7, and 12, on the line through T. 58 S., bet. Rs. 37 and 38 E. is marked by a pine post, 4 ft. long, 5 ins. square, set by a local surveyor.

At point for cor.

Set a brass tablet,  $3\frac{1}{2}$  ins. diam., 3 ins. stem, embedded in an irregular conical concrete monument, 18 ins. diam. at base, 12 ins. high, firmly set 6 ins. deep, in coral rock, with top mkd.

T 58 S.	
R 37 E	R 38 E
S 1	S 6
S 12	S 7
1933	

from which

Reestablishment of cor. of secs. 2, 3, 34, and 35, Ts. 52 and 53 S., R. 30 E.  
and  
of cor. of secs. 1, 6, 7, and 12, T. 58 S., Rs. 37 and 38 E.

The remains of the original bearing trees:

A charred pine stump, 12 ins. diam., bears N.  $31\frac{1}{4}^{\circ}$  E., 66 lks. dist.

A stump hole, bears S  $33^{\circ}$  E., 48 lks. dist.

A stump hole, bears S  $49^{\circ}$  W., 149 lks. dist.

A stump hole, bears N.  $21^{\circ}$  W., 130 lks. dist.

And new bearing trees:

A caribbean pine, 8 ins. diam., bears N.  $14\frac{1}{4}^{\circ}$  E., 44 lks. dist.,  
mkd. T 58 S R 38 E S 6 ET.

A caribbean pine, 10 ins. diam., bears S  $80^{\circ}$  E., 13 lks. dist.,  
mkd. T 58 S R 38 E S 7 BT.

A caribbean pine, 10 ins. diam., bears S  $77\frac{3}{4}^{\circ}$  W., 31 lks. dist.,  
mkd. T 58 S R 37 E S 12 BT.

A caribbean pine, 7 ins. diam. bears N.  $26\frac{1}{2}^{\circ}$  W., 25 lks. dist.,  
mkd. T 58 S R 37 E S 1 ET.

~~\_\_\_\_\_~~  
~~\_\_\_\_\_~~

The County Surveyor of Collier County pointed out to me the corner of secs. 2, 3, 34, and 35, on the S. bdy of T. 52 N., R. 30 E.; and also pointed out to me a corner of Ts. 52 and 53 S., Rs. 30 and 31 E. As additional surveying work may be required in this vicinity, and control is difficult to secure, a record is here given for future reference, and possible use.

The official record of the corner of Ts. 52 and 53 S., Rs. 30 and 31 E. calls for a wooden post, with 1 water oak, 1 maple, and 1 ash bearing trees. No evidence of any of these trees were found.

The corner pointed out to me is a wooden post, set alongside a fallen and rotted lightwood post, with 3 pine bearing trees, from 6 to 12 ins. in diameter. One of these trees is dead and one a dead stub. All of the trees have scribe marks. The ring count on these bearing trees could not be counted exactly, but they were marked about 1890, some 11 years after the township corner was established.

The County Surveyor advised me that he had made extensive retracements of section lines in the vicinity, and had found the cor. of secs. 1, 6, 7, and 12, on the E. bdy of T. 53 S., R. 30 E.; and the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, T. 53 S., R. 31 E. in addition to the cor. of secs. 2, 3, 34, and 35, on the S. bdy of T. 52 S., R. 30 E., and that the township cor. referred to above was properly related to all three of the other corners.

The cor. of Ts. 52 and 53 S., Rs. 30 and 31 E., pointed out to me appears to be either a perpetuation of the original corner or a re-establishment of the corner, made about 11 years after the original survey, by some local surveyor. No lines were retraced by me from the corner as it was not needed on the assignment upon which I was engaged.



CERTIFICATE OF UNITED STATES SURVEYOR

I, Willis W. Bandy, HEREBY CERTIFY upon honor that, in pursuance of ~~special~~ instructions bearing date of the 18th day of January, 1933, received from the ~~district cadastral engineer for~~ Associate Supervisor of Surveys, with assignment instructions dated \_\_\_\_\_, I have ~~successfully~~ reestablished the corner of secs. 2, 3, 34, and 35, Ts. 52 and 53 S., R. 30 E., and the corner of secs. 1, 6, 7, and 12, T. 58 S., Rs. 37 and 38 E.

of the Tallahassee Meridian, in the State of Florida, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Washington, D. C.  
April 27, 1933  
*Willis W. Bandy*  
U. S. Surveyor

CERTIFICATE OF APPROVAL

Department of the Interior  
~~CADASTRAL ENGINEERING STAFF OFFICER~~  
Bureau of Land Management  
Washington, D. C. \_\_\_\_\_ 1933, 19\_\_\_\_

The foregoing field notes of the ~~successful~~ reestablishment of the corners of secs. 2, 3, 34, and 35, Ts. 52 and 53 S., R. 30 E., and of secs. 1, 6, 7, and 12, T. 58 S., Rs. 37 and 38 E., Tallahassee Meridian, Florida

executed by Willis W. Bandy, U. S. Surveyor, under ~~special~~ instructions dated January 18, 1933, and assignment instructions dated \_\_\_\_\_, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

~~CADASTRAL ENGINEERING STAFF OFFICER~~  
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in Florida, is a true copy of the original field notes on file in the public survey office.

~~U.S. Supervisor of Surveys~~  
Cadastral Engineering Staff Officer



